



PREMIER FOOD AND MACHINERY.CO.LTD
68/76-77 Moo5 Rama2Rd., Jomthong Dist, Bangkok 10150 Thailand
Tel (66-2)476-6901, 477-1045, 476-9690, 877-0525-7



NATIONNAL RESERVE

(UNIVERSAL ANTI-GLARE BALLOON LIGHT)

PB1000BS



- LED Lamp 1000W x 1 lamps can be used with home electric system 220 Vol/50Hz and generator.
- LED light energy-efficient.
- LED light: Longer life & least 50000 hours of light without replacement, reliable & high performance.
- LED balloon tower, the light source is gentle, calm victims and the injured.
- Instantaneous lighting and instant restrike with no warm up or standby time required, more suitable for rescue and relief.
- LED light maintenance: No need replacing bulb and lamp, no maintenance cost.
- Maintenance free, can be used at any time.
- Energy saving and environment protection: LED light can save 50% fuel than traditional metal halide light.
- Anti-glare, shadow less, high luminance (220,000 lm) and large scale illumination in range of 360°.
- Advertisement can be made on the surface of balloon to improve enterprise's popularity.
- Equipped with generator, more flexibility, more professional.

- Balloon construction: adopted reliable performance & high pressure & cooling-fan & foldable & stronger wind resistance.
- Balloon envelop is made up of exclusive & rain proof & import fabric Nylon materials, better light transmission, rain proof, sun protection, anti-aging and toughness etc.
- Standard equipped with inflatable, high performance tires. More accord with complex traffic environment to use, such as disaster areas.
- Maximum inclination working is not more than 10°.
- Anti-wind for 6m/s.
- The packing box: it's Chinese military weapons special boxes with PP alloy material
- Various kinds of events since it is glare free and shadow less. It has played an important role in the Olympic Games, NBA and Rally Championship, etc.
- In big events such as concerts, celebrations, press conferences, etc. the balloon light tower is highly praised due to its special illumination and decoration effect.



Feature of balloon light

1. SAFE



Glare-free lighting

Balloon Light gives enough light to a work area but eyes are never blinded by glare even if seeing the light directly. It is friendly to surrounding traffic.

2. EFFICIENT



Wide area & 360 degree illumination

Balloon Light can radiate the homogeneous light far and wide from the balloon to all directions.

3. COMFORT



Large light source

Balloon Light that forms less darker shadow is also comfortable for the workers.

4. VERSATILE




Message strip

Since Balloon Light has integral Velcro fastener, "message strip" can be quickly attached with no tools.

BALL TYPE CAR

UNIT: (mm)





PREMIER FOOD AND MACHINERY.CO.LTD
68/76-77 Moo5 Rama2Rd., Jomthong Dist, Bangkok 10150 Thailand
Tel (66-2)476-6901, 477-1045, 476-9690, 877-0525-7



BALLOON LIGHT SPECIFICATIONS

Model		PB410-400BLED		PB1000BA		PB1000BS-LED		PB1000BWS-LED		PB1000B-LED		PB2000B		PB3000B		PB3000BT										
Items	Type	YAMAHA EF1000	HONDA EC2500CX		YAMAHA EF2600FW		HONDA EG4000CX		YAMAHA EF4000FW		HONDA EC2500CX		YAMAHA EF2600FW		YAMAHA EF2600FW		HONDA EG5000CX		PB3000BT KD E6500E		YAMAHA EF5200EFW					
Generator	Rated voltage	220V	220V		230V		220V		220V		220V		230V		220V		230V		220V		220V					
	Rated frequency	50HZ	50HZ		50HZ		50HZ		50HZ		50HZ		50HZ		50HZ		50HZ		50HZ		50HZ					
	Rated output	0.7KVA	2.0KVA		2.0KVA		3.2KVA		2.9KVA		2.0KVA		2.0KVA		2.0KVA		3.2KVA		2.9KVA		4.0KVA		5.5KVA		3.8KVA	
	Maximum output	0.9KVA	2.2KVA		2.3KVA		3.6KVA		3.3KVA		2.2KVA		2.3KVA		2.3KVA		3.6KVA		3.3KVA		4.5KVA		5.9KVA		4.5KVA	
	Fuel	93#Gasoline	93#Gasoline		93#Gasoline		93#Gasoline		93#Gasoline		93#Gasoline		93#Gasoline		93#Gasoline		93#Gasoline		Diesel		Gasoline					
	Fuel consumption	0.5L/hr	1.13L/hr		1.2L/hr		2.0L/hr		2.0L/hr		1.13L/hr		1.2L/hr		1.2L/hr		2.0L/hr		2.0L/hr		2.5L/hr		2.7L/hr		2.6L/hr	
	Working hours	7.7hr	13hr		10hr		11.9hr		11.9hr		13hr		10hr		10hr		11.9hr		11.9hr		9.5hr		37hr		9.7hr	
	Fuel tank capacity	3.8L	15L		12L		25L		24L		15L		12L		12L		25L		24L		24L		100L		25L	
	Net weight	23kg	45kg		42kg		79kg		71kg		45kg		42kg		42kg		79kg		71kg		82.5kg		100kg		88kg	
	Light Tower Body	Watt x number	180W x 1Lamps	1,000W x 1Lamps		LED 1000w		LED 1000w		LED 1000w		LED 1,000W		1,000W x 2Lamps		1,000W x 3Lamps		1,000W x 3Lamps								
Total luminousness		36,000lm	110,000lm		220,000lm		220,000lm		220,000lm		220,000lm		220,000lm		330,000lm		330,000lm									
Number of expandable		2	Bend type		3		4		4		4		5		5		3									
Length of expandable		2,750mm	1,385-3,630mm		1,725-6,100mm		1,280-4,170mm		2,220-4,950mm		2,220-5,770mm		3,000-6,100mm		Max 9.2m											
Retracted LWH		1,100 x 550 x 800mm	--		---		530 x 530 x 1,280mm		1080 x 780 x 1,660mm		1,160 x 830 x 1,670mm		1,530 x 950 x 2,200mm		4,570 x 1,550 x 1,500mm											
Maximum inclination		< 10°	< 10°		< 10°		< 10°		< 10°		< 10°		< 10°		< 10°											
Anti-wind		≤6	≤6		≤6		≤6		≤6		≤6		≤6		≤6		≤8									
Total weight		45kg	59kg		70kg		75kg		135kg		208kg		308kg		720kg											

FLOODLIGHT SPECIFICATIONS

Model		PB420F-LED	PB420-LED	PB440-LED	PB1200-LED	PB1300	PB1400TMW	PB1400THW	PB1600THWH-L	PB1600THW-LED	PB1800THWH-L-LED
Items	Type	YAMAHA EF2600FW	YAMAHA EF2600FW	YAMAHA EF2600FW	YAMAHA EF2600FW	HONDA EG5000CX	DAISHIN SGB700H-Sa	KUBOTA D1105	KUBOTA D1703	KUBOTA D1105	KUBOTA D1105
Generator	Rated voltage	220V	220V	220V	220V	230V	220V	220V	220V	220V	220V
	Rated frequency	50HZ	50HZ	50HZ	50HZ	50HZ	50HZ	50HZ	50HZ	50HZ	50HZ
	Rated output	2.0KVA	2.0KVA	2.0KVA	2.0KVA	4.0KVA	5.5KVA	8.4KVA	12.8KVA	8.4KVA	8.4KVA
	Maximum output	2.3KVA	2.3KVA	2.3KVA	2.3KVA	4.5KVA	6.0KVA	9.5KVA	15KVA	9.5KVA	9.5KVA
	Fuel	93#Gasoline	93#Gasoline	93#Gasoline	93#Gasoline	93#Gasoline	93#Gasoline	Diesel	Diesel	Diesel	Diesel
	Fuel consumption	1.2L/hr	1.2L/hr	1.2L/hr	1.2L/hr	2.5L/hr	2.8L/hr	2.3L/hr	2.8L/hr	2.3L/hr	2.3L/hr
	Working hours	10hr	10hr	10hr	10hr	9.5hr	9hr	48hr	37hr	48hr	48hr
	Fuel tank capacity	12L	12L	12L	12L	24L	25L	105L	105L	105L	105L
	Net weight	42kg	42kg	42kg	42kg	82.5kg	85kg	142kg	155kg	142kg	142kg
Light Tower Body	Watt x number	LED180x2	LED180x2	LED180x4	LED400x2	1,000W x 3 Lamps	1,000W x 4 Lamps	1,000W x 4 Lamps	1,000W x 6 Lamps	LED400W x 6	LED400W x 8
	Total luminousness	72,000lm	72,000lm	144,000lm	220,000lm	330,000lm	440,000lm	440,000lm	660,000lm	660,000lm	880,000lm
	Number of expandable	2	4	4	4	5	3	3	3	3	2
	Length of expandable	1550-2850mm	1,820-4,650mm	1,820-4,650mm	1,880-4,650mm	2,600-6,100mm	Max 9.0m	Max 9.0m	Max 9.2m	Max 9.4m	Max 9.5m
	Retracted LWH	880 x 420 x 1550mm	1080 x 780 x 1,660mm	1080 x 780 x 1,660mm	1080 x 780 x 1,660mm	1,160 x 630 x 1,800mm	4,570 x 1,550 x 1,500mm	4,570 x 1,650 x 1,900mm	4,570 x 1,750 x 2,100mm	4,670 x 1,750 x 2,200mm	5,300 x 2,000 x 2,400mm
	Maximum inclination	< 10°	< 10°	< 10°	< 10°	< 10°	< 10°	< 10°	< 10°	< 10°	< 10°
	Anti-wind	≤6	≤6	≤6	≤6	≤6	≤8	≤8	≤8	≤8	≤8
	Total weight	79.5kg	125kg	135kg	142kg	239kg	950kg	1150kg	1250kg	1350kg	1550kg



PREMIER FOOD AND MACHINERY.CO.LTD
68/76-77 Moo5 Rama2Rd., Jomthong Dist, Bangkok 10150 Thailand
Tel (66-2)476-6901, 477-1045, 476-9690, 877-0525-7



Certificate

LITEMAN is committed to developing practical lighting solutions and has received CE Certificate, ISO9001 Certificate, and ISO14001 Certificate.

