



## NATIONNAL RESERVE

### PB1200

- Metal Halite Lamp 1000W x 2 lamps can be used with home electric system 220 Vol/50Hz and generator.
- High luminance (220,000 lm).
- Light pollution-free. It protects the environment and improves construction conditions.
- Applicable for the safety construction of highways, expressways and airport.
- Equipped with generator available for diesel and gasoline engine, more flexibility, more professional.
- Adopts manual mechanical lifting mast: 5 stages up to 6.1m, 360° rotation and 120° turn over.
- Safety Winch combine with the green winch with steel wire rope and the green lid.
- Mast Safety Lock: catches the mast in the event of the lifting wire rope breaking to protect the fallen of mast and lamps.
- Tractive design; loading and unloading configuration: hoisting ring & forklift.
- Structure: The Chassis made from Galvanizing Q235 Cold Rolled Steel. The Mast made from Stainless Steel 304. Stronger, rustproof and more durable.
- There are Outriggers with dual structures and directions and easy-moving with footbrake.
- Standard equipped with inflatable, high performance tires. More accord with complex traffic environment to use, such as disaster areas.
- Maximum inclination working is not more than 10°.
- Anti-wind for 6m/s.
- 2017 models, Whole stamping process chassis, stronger, more durable.







PREMIER FOOD AND MACHINERY.CO.LTD  
 68/76-77 Moo5 Rama2Rd., Jomthong Dist, Bangkok 10150 Thailand  
 Tel (66-2)476-6901, 477-1045, 476-9690, 877-0525-7



# PB1200



6 units can be loaded on a 2t truck

Tel. 02-476-6901, 098-256-7756

Mr. NORAPOL H.

h.norapol@preservefood.net

# Metal Halite VS Halogen



### Metal Halide (1000W)

- 110,000 lumen
- 5.2 A
- 15 minutes
- 10,000 hours
- 130 euro

- BRIGHTNESS
- REQUIRED AMPERAGE \*
- RESTRIKE TIME
- LIFE HOURS
- LAMP COST

### Halogen (1000W)

- 27,000 lumen
- 20.2 A
- 0 min.
- 300 hours
- 8 euro

### Characteristic and lamp cost

- Metal halide bright more than 4 times
- Metal halide safe 75%
- Halogen no warm up time
- Metal halide life hours more than 5 times

Electricity cost : 0.1 euro / KWh  
 Running time : 500 hours / year


### Running Cost

	Metal Halide	Halogen
Lamp cost	130 euro	8 euro
Lamp life	10000 hours	300 hours
Required lamp power	1000W	3889W
Energy cost	50 euro / year	194 euro / year
Lamp cost	6.5 euro / year	13.3 euro / year
Lamp-replacement labor cost	0.3 euro / year	10.4 euro / year
<b>TOTAL ANNUAL COST</b>	<b>56.8 euro</b>	<b>217.7 euro</b>

\* Lamp-replacement cost assumes 15 min. per lamp at 25 euro / hour

## PROJECTION LIGHTING VEHICLE

UNIT: (mm)







## BALLOON LIGHT SPECIFICATIONS

Model		PB410-400BLED	PB1000BA		PB1000BS-LED		PB1000BWS-LED		PB1000B-LED	PB2000B		PB3000B	PB3000BT	
Items	Type	YAMAHA EF1000	HONDA EC2600CX	YAMAHA EF2600FW	HONDA EG4000CX	YAMAHA EF4000FW	HONDA EC2600CX	YAMAHA EF2600FW	YAMAHA EF2600FW	HONDA EG4000CX	YAMAHA EF4000FW	HONDA EG6000CX	PB3000BT KD E6600E	YAMAHA EF3200EFW
Generator	Rated voltage	220V	220V		230V	220V	220V		220V	230V	220V	230V	220V	220V
	Rated frequency	50HZ	50HZ		50HZ	50HZ	50HZ		50HZ	50HZ	50HZ	50HZ	50HZ	50HZ
	Rated output	0.7KVA	2.0KVA	2.0KVA	3.2KVA	2.9KVA	2.0KVA	2.0KVA	2.0KVA	3.2KVA	2.9KVA	4.0KVA	5.5KVA	3.8KVA
	Maximum output	0.9KVA	2.2KVA	2.3KVA	3.6KVA	3.3KVA	2.2KVA	2.3KVA	2.3KVA	3.6KVA	3.3KVA	4.5KVA	5.9KVA	4.5KVA
	Fuel	93#Gasoline	93#Gasoline		93#Gasoline		93#Gasoline		93#Gasoline	93#Gasoline		93#Gasoline	Diesel	Gasoline
	Fuel consumption	0.5L/hr	1.13L/hr	1.2L/hr	2.0L/hr	2.0L/hr	1.13L/hr	1.2L/hr	1.2L/hr	2.0L/hr	2.0L/hr	2.5L/hr	2.7L/hr	2.6L/hr
	Working hours	7.7hr	13hr	10hr	11.9hr	11.9hr	13hr	10hr	10hr	11.9hr	11.9hr	9.5hr	37hr	9.7hr
	Fuel tank capacity	3.8L	15L	12L	25L	24L	15L	12L	12L	25L	24L	24L	100L	25L
	Net weight	23kg	45kg	42kg	79kg	71kg	45kg	42kg	42kg	79kg	71kg	82.5kg	100kg	86kg
	Light Tower Body	Watt x number	180W x 1Lamps	1,000W x 1Lamps		LED 1000w		LED 1000w		LED 1,000W	1,000W x 2Lamps		1,000W x 3Lamps	1,000W x 3Lamps
Total luminousness		36,000lm	110,000lm		220,000lm		220,000lm		220,000lm	220,000lm		330,000lm	330,000lm	
Number of expansion		2	Bend type		3		4		4	5		5	3	
Length of expansion		2,750mm	1,385-3,630mm		1,725-6,100mm		1,280-4,170mm		2,220-4,950mm	2,220-5,770mm		3,000-6,100mm	Max 9.2m	
Retracted LWH		1,100 x 550 x 800mm	---		---		530 x 530 x 1,280mm		1080 x 780 x 1,660mm	1,160 x 830 x 1,670mm		1,530 x 950 x 2,200mm	4,570 x 1,550 x 1,500mm	
Maximum inclination		< 10°	< 10°		< 10°		< 10°		< 10°	< 10°		< 10°	< 10°	
Anti-wind		≤6	≤6		≤6		≤6		≤6	≤6		≤6	≤8	
Total weight		45kg	59kg		70kg		75kg		135kg	208kg		308kg	720kg	

## FLOODLIGHT SPECIFICATIONS

Model		PB420F-LED	PB420-LED	PB440-LED	PB1200-LED	PB1300	PB1400TMW	PB1400THW	PB1600THW-HL	PB1600THW-LED	PB1600THW-HL-LED
Items	Type	YAMAHA EF2600FW	YAMAHA EF2600FW	YAMAHA EF2600FW	YAMAHA EF2600FW	HONDA EG6000CX	DAISHIN SGB700H-5a	KUBOTA D1105	KUBOTA D1703	KUBOTA D1105	KUBOTA D1105
Generator	Rated voltage	220V	220V	220V	220V	230V	220V	220V	220V	220V	220V
	Rated frequency	50HZ	50HZ	50HZ	50HZ	50HZ	50HZ	50HZ	50HZ	50HZ	50HZ
	Rated output	2.0KVA	2.0KVA	2.0KVA	2.0KVA	4.0KVA	5.5KVA	8.4KVA	12.8KVA	8.4KVA	8.4KVA
	Maximum output	2.3KVA	2.3KVA	2.3KVA	2.3KVA	4.5KVA	6.0KVA	9.5KVA	15KVA	9.5KVA	9.5KVA
	Fuel	93#Gasoline	93#Gasoline	93#Gasoline	93#Gasoline	93#Gasoline	93#Gasoline	Diesel	Diesel	Diesel	Diesel
	Fuel consumption	1.2L/hr	1.2L/hr	1.2L/hr	1.2L/hr	2.5L/hr	2.8L/hr	2.3L/hr	2.8L/hr	2.3L/hr	2.3L/hr
	Working hours	10hr	10hr	10hr	10hr	9.5hr	9hr	48hr	37hr	48hr	48hr
	Fuel tank capacity	12L	12L	12L	12L	24L	25L	105L	105L	105L	105L
	Net weight	42kg	42kg	42kg	42kg	82.5kg	85kg	142kg	155kg	142kg	142kg
	Light Tower Body	Watt x number	LED180x2	LED180x2	LED180x4	LED400x2	1,000W x 3 Lamps	1,000W x 4 Lamps	1,000W x 4 Lamps	1,000W x 6 Lamps	LED400W x 6
Total luminousness		72,000lm	72,000lm	144,000lm	220,000lm	330,000lm	440,000lm	440,000lm	660,000lm	660,000lm	880,000lm
Number of expansion		2	4	4	4	5	3	3	3	3	2
Length of expansion		1550-2850mm	1,820-4,650mm	1,820-4,650mm	1,880-4,650mm	2,600-6,100mm	Max 9.0m	Max 9.0m	Max 9.2m	Max 9.4m	Max 9.5m
Retracted LWH		880 x 420 x 1550mm	1080 x 780 x 1,660mm	1080 x 780 x 1,660mm	1080 x 780 x 1,660mm	1,160 x 830 x 1,800mm	4,570 x 1,550 x 1,500mm	4,570 x 1,650 x 1,900mm	4,570 x 1,750 x 2,100mm	4,670 x 1,750 x 2,200mm	5,300 x 2,000 x 2,400mm
Maximum inclination		< 10°	< 10°	< 10°	< 10°	< 10°	< 10°	< 10°	< 10°	< 10°	< 10°
Anti-wind		≤6	≤6	≤6	≤6	≤6	≤8	≤8	≤8	≤8	≤8
Total weight		79.5kg	125kg	135kg	142kg	239kg	950kg	1150kg	1250kg	1350kg	1550kg






PREMIER FOOD AND MACHINERY.CO.LTD  
 68/76-77 Moo5 Rama2Rd., Jomthong Dist, Bangkok 10150 Thailand  
 Tel (66-2)476-6901, 477-1045, 476-9690, 877-0525-7



## Certificate

LITEMAN is committed to developing practical lighting solutions and has received CE Certificate, ISO9001 Certificate, and ISO14001 Certificate.



Tel. 02-476-6901, 098-256-7756

Mr. NORAPOL H.

h.norapol@preservefood.net