

## S- 5000A TW

High speed lane type  
 Saves floor space and increases production



### Features

- Individually controlled twin lanes
- Dual performance enabling double throughput.
- Different products can be run on each lane or, alternatively, the same product can be run on both lanes.
- Automatic Film Splicer with splice rejection for both lanes as standard.
- Mirror image model is available so with one of each model facing the other, 1 operator can supervise 4 production lines from the same position.
- Compact body saves floor space.
- Various optional devices available

### Specifications

	High speed twin lane HFFS machine
Speed	600~1,000packs/min
Main motor	AC servo motor



PREMIER FOOD AND MACHINERY.CO.LTD  
68/76-77 Moo5 Rama2Rd., Jomthong Dist, Bangkok 10150 Thailand  
Tel (66-2)476-6901, 477-1045, 476-9690, 877-0525-7



Film width	MAX. 250mm Roll Diameter:φ350mm
Cut-off length	60mm~
Product size (Max.)	Width : 100mm Height : 30mm
Standard paint color	Ivory(Baked paint finish)
Power used	3PH 200V 10KVA (Differs according to specification)
Machine weight	Approx 1,500Kg

\*Specifications are subject to change depending on product and film

## Optional equipment

- Printer
- Various automatic feeders

## Optional soft

- On-demand function: (No product, no bag)
- Memory Card (Back-up/Restore Data).
- Calendar Timer (Allows sealer pre-heating and timed shut-down)