



PREMIER FOOD AND MACHINERY.CO.LTD  
68/76-77 Moo5 Rama2Rd., Jomthong Dist, Bangkok 10150 Thailand  
Tel (66-2)476-6901, 477-1045, 476-9690, 877-0525-7



## S - 5000A

## S - 5000A BX

### Features

- Clear 12.1" LCD color touch screen control panel
- Direct servomotor drive film unwind
- Neat and consistent wrapping
- Self-diagnostics for fast response and ease of operation.
- Designed for production versatility
- Quiet and simple to maintain
- Designed for incorporation into a complete production line



### Specifications

Model	S-5000A BX	S-5100A BX
Speed	120packs/min.	
Main motor	AC servo motor	
Film width	MAX450mm	MAX600mm



PREMIER FOOD AND MACHINERY.CO.LTD  
 68/76-77 Moo5 Rama2Rd., Jomthong Dist, Bangkok 10150 Thailand  
 Tel (66-2)476-6901, 477-1045, 476-9690, 877-0525-7



Cut-off length	110~9,999mm	
Product size (Max.)	Width : 200mm Height : 60mm	Width : 280mm Height : 80mm
Standard paint color	Ivory(Baked paint finish)	
Power used	3PH 200V 5KVA (Differs according to specification)	
Machine weight	Approx 1,100Kg	Approx 1,000Kg

Super wide type S-5200A available (Film width :850mm)

\*Specifications are subject to change depending on product and film.

## Specifications

Model	S-5000A	S-5100A
Speed	300packs/min.	200packs/min.
Main motor	AC servo motor	
Film width	MAX450mm	MAX600mm
Cut-off length	110~9,999mm	
Product size (Max.)	Width : 200mm Height : 60mm	Width : 280mm Height : 80mm
Standard paint color	Ivory(Baked paint finish)	
Power used	3PH 200V 5KVA (Differs according to specification)	



PREMIER FOOD AND MACHINERY.CO.LTD  
68/76-77 Moo5 Rama2Rd., Jomthong Dist, Bangkok 10150 Thailand  
Tel (66-2)476-6901, 477-1045, 476-9690, 877-0525-7



Machine weight	Approx 800Kg	Approx 1,000Kg
----------------	--------------	----------------

Super wide type S-5200A available (Film width :850mm)

\*Specifications are subject to change depending on product and film.

## Optional equipment

- Automatic Film Splicer with splice rejection
- "Feather Touch" end seal detection system prevents product or foreign material crushing in the end sealer
- Gas flushing (MAP) device.
- Film edge position controller – prevents snaking
- Printer
- Multiple pitch infeed
- Gusset device – neat & compact end seals
- Various automatic feeders
- Hanging display hole punch
- Oxygen absorber feeder
- Offset center seal
- Onside seal opened

## Optional soft

- On-demand function: (No product, no bag)
- Mis-position, non-cut function – Disables end sealer if product is out of position
- Memory Card (Back-up/Restore Data)
- Calendar Timer (Allows sealer pre-heating and timed shut-down)