

S - 5600A

S - 5600A BX

Inverted High-Speed Horizontal Form-Fill-Seal Machines Ideal for loose, sticky or crumbly items



Features

- Clear 12.1" LCD color touch screen control panel.
- Suitable for wrapping multiple loose products without a tray and stick-shaped products.
- Soft products are gently wrapped.
- Self-diagnostics for fast response and ease of operation.
- High quality, high speed wrapping.
- Designed for production versatility.
- Quiet and simple to maintain.
- Ideal for small items for high-speed packaging

Specifications

Box motion end seal

Model	S-5600A BX	S-5700A BX (Wide type)
Speed	120packs/min	



PREMIER FOOD AND MACHINERY.CO.LTD
 68/76-77 Moo5 Rama2Rd., Jomthong Dist, Bangkok 10150 Thailand
 Tel (66-2)476-6901, 477-1045, 476-9690, 877-0525-7



Main motor	AC servo motor	
Film width	MAX 450mm	MAX 600mm
Cut-off length	110~9,999mm	
Product size (Max.)	Width : 200mm Height : 60mm	Width : 280mm Height : 80mm
Standard paint color	Ivory (A different color may be specified as an option)	
Power used	3PH 200V 5KVA (Differs according to specification)	
Machine weight	Approx 1,000Kg	Approx 1,100Kg

Super width type: We also have S-5800BX(Film width :850mm)

Rotary end seal

Model	S-5600A	S-5700A (Wide type)
Speed	120packs/min	
Main motor	AC servo motor	
Film width	MAX 450mm	MAX 600mm
Cut-off length	60~9,999mm	
Product size (Max.)	Width : 200mm Height : 60mm	Width : 280mm Height : 60mm
Standard paint color	Ivory(Baked paint finish)	



PREMIER FOOD AND MACHINERY.CO.LTD
68/76-77 Moo5 Rama2Rd., Jomthong Dist, Bangkok 10150 Thailand
Tel (66-2)476-6901, 477-1045, 476-9690, 877-0525-7



Power used	3PH 200V 5KVA (Differs according to specification)	
Machine weight	Approx 1,000Kg	Approx 1,100Kg

Super width type: We also have S-5800A(Film width :850mm)

*Specifications are subject to change depending on product and film.

Optional equipment

- Automatic Film Splicer with splice rejection
- Printer
- Inner protective film strip
- Gusset device – neat & compact end seals
- Various automatic feeders
- Hanging display hole punch
- Oxygen absorber feeder
- One end open end seal
- Gas flushing (MAP) device

Optional soft

- On-demand function: (No product, no bag)
- Mis-position, non-cut function – Disables end sealer if product is out of position
- Memory Card (Back-up/Restore Data).
- Calendar Timer (Allows sealer pre-heating and timed shut-down)