

SW- 4500Z

HFFS machine for 4 side seal package 4-side seal machine with aipper for airtight reclosure



Features

- Clear 12.1" LCD color touch screen control panel
- (independent screens for Operation and Temperature control)
- Eight axis motion control system.
- High integrity, attractive packaging.
- Ideal for Aluminum laminated film and paper aluminum film.
- Designed for high integrity packaging, validation support and for ease of maintenance.
- Planned for integration in a complete production line.

Specifications

Model	SW4500Z (standardType)	SHW4500Z (High-speed type)
Speed	80bags/min	110bags/min
Main motor	AC servo motor	
Film width	MAX 470mm	
Cut-off length	100mm~250mm	120mm~150mm
Product size (Max.)	Width : 140mm Height : 10mm length : 140mm	Width : 140mm Height : 10mm length : 140mm



PREMIER FOOD AND MACHINERY.CO.LTD
68/76-77 Moo5 Rama2Rd., Jomthong Dist, Bangkok 10150 Thailand
Tel (66-2)476-6901, 477-1045, 476-9690, 877-0525-7



Standard paint color	Ivory (A different color may be specified as an option)
Power used	3PH 200V 12KVA (Differs according to specification)
Machine weight	Approx 5,000Kg

- End seal area: Box motion + rotary + die cutter (triple head type)
- Film supply section : Independent type (with Automatic Film Splicer and splice rejection)
- With fixed tension control (powder brake control)
- Zipper feeding device: zipper sealing area, zipper melt/crush area, warm water chiller for zipper seal
- Film scrap collection device : Scrap chopping cutting method
- Detection devices: "Feather Touch" end seal detection system prevents product or foreign material crushing in the end sealer, Mis-position, non-cut function – Disables end sealer if product is out of position, Zipper closure fault detection
- On-demand function: (No product, no bag)
- Automatic Film Splicer with splice rejection

Optional equipment

- Various printer, impress coding and inspection devices
- Validation documentation
- Film edge position controller – prevents snaking
- Quick change air shaft film mounting
- Die cutter change trolley
- Automatic zipper splicer
- X-ray Mis-position, non-cut function – Disables end sealers if product is out of position